

## Adhesive resin

### S-542

#### Features:

- The curing speed is moderate.
- Good adhesion
- good toughness

#### Product specifications:

|                         |                                     |
|-------------------------|-------------------------------------|
| Appearance              | Pale yellow semi-transparent liquid |
| Component               | Adhesive resin                      |
| Non volatiles           | 50% (theoretical value)             |
| degree of functionality | 2                                   |
| Color (Fe-Co)           | $\leq 1$                            |
| Viscosity(cps/25℃)      | 2000-7000                           |
| Acid value (mgKOH/g)    | /                                   |

#### Application:

- Vacuum electroplated topcoat
- Ink, wood finish, plastic coatings

#### Precautions:

Avoid contact with skin, eyes and clothing. Please wear protective gloves during operation. In case of leakage, wipe it clean with a cloth and then wash it with ethyl acetate. For detailed instructions, please refer to the Material Safety Data Sheet (MSDS).

#### Packing:

Net weight 220 KG/barrel

#### Storage:

The product is packaged in a sealed container. The storage temperature is recommended to be within the range of 0~40℃. It should be stored in a cool place, a

way from the sun and rain, and away from fire. The shelf life of this product is 6 months from the date of production. Frost should be avoided when the temperature is below 0°C in winter. Please conduct necessary tests before use.