

## urethane acrylate

### S-563

#### Features:

- fast curing
- The powder has good wetting properties and is easy to be ground down
- Resistant to yellowing and with good toughness

#### Product specifications:

|                         |                                 |
|-------------------------|---------------------------------|
| Appearance              | Light yellow transparent liquid |
| Component               | Aliphatic polyurethane acrylate |
| Non volatiles           | 100% (theoretical value)        |
| degree of functionality | 3                               |
| Color (Fe-Co)           | $\leq 1$                        |
| Viscosity(cps/25℃)      | 30000-65000                     |
| NCO%                    | $<0.3$                          |

#### Application:

- Ink
- wood lacquer, paper printing

#### Precautions:

Avoid contact with skin, eyes and clothing. Please wear protective gloves during operation. In case of leakage, wipe it clean with a cloth and then wash it with ethyl acetate. For detailed instructions, please refer to the Material Safety Data Sheet (MSDS).

#### Packing:

Net weight 220 KG/barrel

#### Storage:

The product is packaged in a sealed container. The storage temperature is recommended to be within the range of 0~40℃. It should be stored in a cool place, a

way from the sun and rain, and away from fire. The shelf life of this product is 6 months from the date of production. Frost should be avoided when the temperature is below 0°C in winter. Please conduct necessary tests before use.